

NEOSPATOULA AKRYLIKI FINE

SUITABLE FOR LEVELLING PLASTERBOARD
AND OTHER APPLICATION

SUB/10 | SUBSTRATES (SURFACE PREPARATION)



DESCRIPTION

NEOSPATOULA AKRYLIKI FINE is specially formulated to be used as plaster on walls and plasterboards before each regular finish. Due to its high content of acrylic copolymer it has a very good adhesion to the substrate. NEOSPATOULA AKRYLIKI can be used right out of the container without dilution.

COVERAGE

0.5-1kg/m² depending on the nature of the surface.

STORAGE

Up to 12 months in sealed containers protected from direct sunlight and low temperatures.

DIRECTIONS FOR USE

- The surface used on must be clean from dust, paint, grease and other matters that could affect adhesiveness.
- For a higher adhesiveness of NEOSPATOULA AKRYLIKI FINE, apply 1 coat of NEOCHROM'S NEOPRIMER prior to plaster. Allow to dry for 2-3 hours at 20°C and apply a thin layer with a finishing trowel.
- If necessary, apply 1 more coat of NEOSPATOULA AKRYLIKI FINE after a 5-6 hour drying time at 20°C.

DECORATION

- The plastered surface to be decorated must be dry before application.
- Prior to the final decoration, it is recommended to use 1 coat of NEOCHROM'S NEOPRIMER or NEOCHROM'S NEOSTRONG PRIMER with mixing ratio 1:1 to control absorbency.
- Paint, fine or thick grain coating can then be applied on this surface.

TECHNICAL SPECIFICATIONS

Colour:	White
Solids:	72-74%
Mixture pH:	6-7
Temperature during application:	From +5°C to +35°C
Adhesive strength:	>0,2N/mm ²
Water absorption:	W1

PACKAGING:

0.75, 3.5, 7, 14 AND
25KG PLASTIC CONTAINERS

