



ASBESTOSEAL

SEALING COATING

ISL/09 | INSULATING – WATERPROOFING MATERIALS

DESCRIPTION

ASBESTOSEAL is a high quality acrylic elastomeric material, specially formulated to seal and insulate asbestos sheets and boards (Asbestos Encapsulation). ASBESTOSEAL's protective layer essentially captures asbestos's dangerous fibres, stopping them from being released and airborne, and from potentially being inhaled and causing health risks. ASBESTOSEAL remains strong for years after its application and is not affected by weather changes and in addition provides a high degree of thermal and water insulation for the surface.

COVERAGE

Varies around 250-350g/m² depending on the surface absorbency

STORAGE

On wood pallets, in covered areas, protected from direct sunlight and low temperatures.

DIRECTIONS FOR USE

- Surfaces to be treated with ASBESTOSEAL must be clean and free from dust, salts, loose materials and grease.
- ASBESTOSEAL is water soluble and it is applied by a spray gun, brush or paint roller on clean and dry surfaces, in minimum two coats.
- Always apply on both sides of the sheets to avoid potential differential carbonisation of the asbestos-cement material.
- It is suitable for outdoor and indoor surfaces – Its mixing ratio is ASBESTOSEAL 85% - Water 15%.

TECHNICAL SPECIFICATIONS

Colour:	White and a large range of made to order colours
Waterproofing:	Complete
Humidity resistance:	Excellent
Acids and alkalis resistance:	Fairly good
Adhesiveness:	Excellent
Temperature during application:	From +5°C to +35°C



PACKAGING:

18LT PLASTIC CONTAINERS

