

NEOLUX

ALUMINIUM PAINT (REFLECTIVE)

ISL/08 | INSULATING-WATERPROOF MATERIALS



DESCRIPTION

NEOLUX is a sun-proofing and decorative roof coating. It can be applied on asphalt surfaces but also on metal surfaces. It has a high UV ray reflective factor and reduces the cracking and the mobility of asphalt material that are subject to wear from UV radiation. It can also be used on asphalt sheets.

COVERAGE

Approximately 6 – 8m²/lt.

STORAGE

Up to 12 months in sealed containers protected from direct sunlight and low temperatures.

DIRECTIONS FOR USE

- NEOLUX is applied with a brush or a paint roller.
- The surface to be applied on must be dry and clean.
- Repair any cracks, damages or holes.
- Fill all cracks, joints etc with NEOCHROM's NEOFLEX.
- To achieve an even layer of the material, NEOLUX must be thoroughly stirred prior and during application.
- If needed, it can be diluted with paint thinner.
- It required 2-4 hours for it to be dry on the surface and approximately 24 hours for complete drying, depending on the weather conditions.

TECHNICAL SPECIFICATIONS

| | |
|--|--------------------|
| Colour: | Aluminium |
| Mixture specific gravity: | 0,95 kg/lt |
| It is not toxic, but ensure proper ventilation when handling | ✓ |
| Temperature during application: | From +5°C to +35°C |



PACKAGING:

2.5 AND 20LT METALLIC CANISTERS

